

Impregnator – Technical Data Sheet

• Product Description:

BANAS IMPREGNATOR is used for water and dirt repellent treatment of absorbent natural and artificial stones. The Product is free from solvents and is odourless. Neutral pH value, therefore suited for all surfaces. The colour will normally not be changed. It can be used on humid surfaces with excellent results.

• Key Features:

- o Effective on both Natural and polished surfaces
- o Applicable on humid stone
- Neutral pH value
- o Odourless

• Suitable stone types:

Natural & Artificial stones, Terrazzo, interior and exterior ceramic and porcelain tiles. Especially suited for surfaces with residual humidity mainly outdoors and for the use in polishing lines of the stone industry

• Limitations to the product:

Innovative dirt and water repellent for a short period of time.

• Installation & Application:

- The surface must be clean, dry to a large extent and free from all layers
- To determine consumption, colour enhancement and efficiency prepare a sample area
- Working temperature 5 25°C (40 77°F); avoid direct solar radiation until hardening is completed.
- Depending on absorptive capacity apply 1 2 times fully and evenly with a brush, mop or spraying device
- Surplus material must not dry on the surface but should be removed with a suitable cloth or fabric

• Drying Time:

- After application, leave it for 2-3 hours
- The water repellent effect develops after 4 6 hours
- After application, protect against rain for approx. 24 hours

- Safety:
 - For proper waste disposal, the container must be completely emptied.
 - Observation of Technical Data Sheet is mandatory (www.banasstones.com).
 - Wear suitable protective gloves.
 - o Use Tightly sealed goggles

• Cleaning of equipment:

Clean tools with soap and water immediately after use.

• Health Precautions:

Causes serious eye damage. Wear protective gloves/protective clothing/eye protection/face protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

o Coverage:

Up to 25 $\ensuremath{\text{m}^2\/l}\xspace$, depending on absorptive capacity of the stone

- Sizes Available: 1000ml (0.26 gal.)
- Storage:

2 years if stored in cool place free from frost in its tightly closed original container

- Please Note:
 - Always test in a small inconspicuous area before applying to the total area.
 - Read material safety data sheet before handling or using this product

