




BLU 60 mm

DESCRIPTION: Slab **TEXTURE:** Smooth and HD² smooth

PALLET OVERVIEW



NOTES

See page 31 to 33 for more technical information. When used in a permeable pavement application, see page 99 to 104 for more technical information.


See page 28 for more information about applications.

JOINT WIDTH: 9/32" (7 mm)
% OF SURFACE OPENING: 3.0 %
INFILTRATION RATE: 570 in./hr (14 475 mm/hr)


Specifications per pallet	Imperial	Metric
Cubing	116.82 ft²	10.96 m ²
Approx. Weight Smooth	3 170 lbs	1 438 kg
Approx. Weight HD ² Smooth	3 295 lbs	1 495 kg
Number of rows	11	
Coverage per row	10.62 ft ²	0.99 m ²
Linear coverage per row	9.81 lin. ft	3.02 lin. m

Unit dimensions	in	mm	Units/pallet
A	Height: 2 3/8	60	44 units
	Width: 13	330	
	Length: 6 1/2	165	
B	Height: 2 3/8	60	44 units
	Width: 13	330	
	Length: 13	330	
C	Height: 2 3/8	60	22 units
	Width: 13	330	
	Length: 19 1/2	495	


01 | Modular pattern



02 | Modular pattern



03 | Linear pattern



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.

Chestnut Brown

HD² Smooth
Smooth



Champlain Grey

HD² Smooth
Smooth



Beige Cream

Smooth




Greyed Nickel

HD² Smooth
Smooth



Shale Grey


HD² Smooth
Smooth



Onyx Black

HD² Smooth
Smooth






BLU 60 mm (6"×13")

DESCRIPTION: Slab **TEXTURE:** Smooth and HD² Smooth

PALLET OVERVIEW



Specifications per pallet		Imperial	Metric
Cubing		116.05 ft²	10.78 m ²
Approx. Weight Smooth		3 138 lbs	1 423 kg
Approx. Weight HD ² Smooth		3 147 lbs	1 427 kg
Number of rows		11	
Coverage per row		10.55 ft ²	0.98 m ²
Linear coverage per row	Depth	19.5 lin. ft	5.94 lin. m
	Length	9.75 lin. ft	2.97 lin. m



Unit dimensions	in	mm	Units/pallet
Height	2 3/8	60	198 units
Width	13	330	
Length	6 1/2	165	


NOTES

See page 31 to 33 for more technical information. When used in a permeable pavement application, see page 99 to 104 for more technical information.


See page 28 for more information about applications.

JOINT WIDTH: 9/32" (7 mm)
% OF SURFACE OPENING: 4.6 %
INFILTRATION RATE: 570 in./hr (14 475 mm/hr)


08 | Linear pattern




09 | Linear pattern



10 | Parquet pattern



11 | Herringbone pattern



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.

Chocolate Brown

Smooth



Chestnut Brown

HD² Smooth
Smooth




Champlain Grey

HD² Smooth
Smooth



Beige Cream

Smooth




Greyed Nickel

HD² Smooth
Smooth



Shale Grey

HD² Smooth
Smooth



Onyx Black

HD² Smooth
Smooth

