



Brussels Block®

1-800-UNILOCK | UNILOCK.COM

UNILOCK
PAVERS & WALLS

BRUSSELS BLOCK®

CLASSIC



LIMESTONE



MAHOGANY



SANDSTONE



SIERRA



MIDNIGHT CHARCOAL

XL, Standard and Fullnose only

PRODUCT ATTRIBUTES

Visual Appearance	Original tumbled paver. Timeless warmth, relaxed appearance.
Finish	Tumbled and weathered finish.

PRODUCT SPECIFICATIONS



XL STONE
8 $\frac{1}{8}$ x 13 $\frac{3}{8}$ x 2 $\frac{3}{4}$ "
208 x 348 x 70mm



STANDARD STONE
6 $\frac{1}{8}$ x 8 $\frac{1}{8}$ x 2 $\frac{3}{4}$ "
173 x 208 x 70mm



HALF STONE
4 $\frac{1}{8}$ x 6 $\frac{1}{8}$ x 2 $\frac{3}{4}$ "
104 x 173 x 70mm




FULLNOSE COPING
5 $\frac{7}{8}$ x 11 $\frac{1}{8}$ x 2 $\frac{3}{4}$ "
150 x 300 x 70mm

Limestone, Sandstone and Midnight Charcoal only


Please see Steps, Treads and Coping section, page 146 for more details.

EDGE DETAILS




TUMBLLED EDGE


LAYING PATTERNS




BRUSSELS AF
40% XL, 40% Standard,
20% Half



BRUSSELS O
33% Half Stone, 67%
Standard



BRUSSELS P
67% Standard, 33% Half



BRUSSELS W
18% Half Stone, 23%
Standard, 59% XL

JNIOCK

RECOMMENDED SAND



Gator G2 Super Sand

- | Rain safe after 15 mins
- | Sets above 32° F/ 0° C
- | Can be used for joints up to a max of 2"
- | Dust free and haze free
- | Requires only one watering
- | Two colours: Beige, Slate Grey

Coverage:

Colour	Narrow Joints	Wide Joints
Beige, Slate Grey 50lb. bag	65-85 sqft	22-42 sqft

RECOMMENDED SEALER



Gator Natural Look Sealer

- | Water-based
- | Zero gloss finish
- | Multi purpose
- | Rain safe after 24 hours

Coverage:

Size	Area
3.78 L / 1 U.S. gal.	175 sqft
18.9 L. / 5.28 U.S. gal.	875 sqft

TECHNICAL INFORMATION

ASTM C936 Standard Specifications for Solid Concrete Interlocking Paving Units

Conforms to:

- C140 for Absorption 5% avg - 7% max
- Compressive Strength > 7,200 PSI avg.
- C67 for Freeze-thaw Durability
- C418 for Abrasion Durability
- Dimensional Accuracy **+/- 3mm**

Test results available upon request

Meets the U.S. Architectural & Transportation Barrier Compliance Board Slip-Resistance Surfaces Advisory Guidelines

TECHNICAL ADVANTAGES

CLASSIC

Budget-friendly. Utilize a traditional product mix of large and small aggregates that's consistent from top to bottom with colour mixed throughout

ANTIQUED FINISH

Distressed, timeworn finish

DRIVE FRIENDLY

Can handle vehicular loads

Ask about our base stabilization system

PRODUCT DATA

Stones & Bundling	Unit	SqFt Per				Per Bundle		Soldier LnFt Per			Sailor LnFt per			Units Per			Lbs Per		
	Thickness	Bundle	Layer	Sections	Stone	Layers	Sections	Unit	Section	Bundle	Unit	Section	Bundle	SqFt	Sections	Bundle	Layer	Section	Bundle
Ayr manufacturing																			
XL	2¾" (70mm)	95.94	11.99	31.98	0.80	8	3	1.17	27.3	81.9	0.70	45.7	137.0	1.25	40	120	378	1,008	3,024
Standard	2¾" (70mm)	95.94	11.99	15.99	0.40	8	6	0.70	22.7	136.2	0.58	27.3	163.8	2.50	40	240	383	510	3,064
Half	2¾" (70mm)	99.79	12.47	14.26	0.20	8	7	1.72	24.57	172.00	2.95	42.04	294.30	5.05	72	504	399	446	3,124

Notes: All measurements are nominal. Contact your Unilock Territory Manager or call 1-800-UNILOCK for further information. *For custom options, please contact your Unilock Territory Manager.

APPLICATIONS



Pedestrian



Residential Vehicular



Borders and Accents



Wall pairing suggestion- Brussels Dimensional Stone - matching colour and finish

SOLAR REFLECTIVE INDEX (SRI) TESTING DETAILS

Product	Solar Reflectance	SRI
Limestone	0.28	29
Sandstone	0.41	46

LEED INFORMATION

Materials & Resources: LEED V4:

Building Product Disclosure and Optimization

Sourcing of Raw Materials - Sourcing of Raw Materials and Extraction • **1 point**

Sourcing of Raw Materials - Leadership Extraction Practices • **1 point**

Material Ingredient Reporting - Material Ingredient Reporting • **1 point**

Material Ingredient Reporting - Material Ingredient Optimization • **1 point**

Environmental Product Declaration • **1 point**

*Paver Maintenance Tips:

- Equip plow scrapers and blades with shoes or high-density plastic blades to reduce the risk of damaging paver joints and the surface
- Only apply min. amount of de-icing salts necessary to melt the snow and ice. Remove excess salt after ice melts
- Regular cleaning routine should include sweeping or blowing loose debris from the pavement surface, and less frequently, deep cleaning with cleaning products and/or water
- Unilock pavers do not require sealing, however, some people choose to do so for aesthetic purposes

*Things to know:

Efflorescence is a naturally occurring calcium salt that can sometimes appear on the surface of concrete and clay products. Efflorescence does not affect the structural integrity of concrete, it is a purely aesthetic issue that typically disappears with no further intervention after a season of rainfall. If desired, the process can be accelerated by washing the surface with an Efflorescence Remover.